## DATA SHEET. Model: QR-3BRY.

Rechargeable LED handlamp of the QR Series.







### **Description**

Watertight and highly durable rechargeable LED handlamp for railway and industrial purpose. It incorporates an electronic circuit with microprocessor that allows programmable functions. White, red and yellow illumination through a RGBW high-power LED in the main light source.

### **Technical characteristics**

Color main light source	White-Red-Yellow
Usage temperature	From -10°C to 50°C
Electrical insulation	Class III
Weight	800 g
Protection rating	IP67 – IK08
Battery	Li-lon 7.2 V – 2.6 Ah

	Chargers C-64 series
Without signaling	N/A
With signaling	2 push buttons
Housing material	Technical polymers
Housing color	Black
Light beam	50% at ± 5.4°
	10% at ± 8.9°

Charging status control	Red	0% – 2	20%
	1 mbor	200/	C00/

Amber 20% – 60% Green 60% – 100% Green flash >100%

Orientation light beam Mobile support
Applicable legislation CE Marking (93/68/CEE):

2014/35/EU 2014/30/EU 2011/65/EU

# **Lighting characteristics**

Power	Low	Nominal	High
Luminous flux	40 lm	100 lm	220 lm
Autonomy	36 h	12 h	4 h
Range	59 m	94 m	139 m
Intensity	876 cd	2,190 cd	4,818 cd


#### **Functions**


Standard programming includes 3 power modes and 3 flashing modes.

Automatic shut-off when the handlamp is placed on the charger.

Automatic switch-on for 3 minutes in case of mains power failure to the charger.

### **Dimensions**





DATA SHEET. Model: QR-3BRY \_ Rev. 00 (July 2024)





