

DATA SHEET. Model: QS-R2B.

Rechargeable LED handlamp of the QS Series.



Description

Watertight and highly durable rechargeable LED handlamp for civil protection and signaling. It incorporates an electronic circuit with microprocessor that allows programmable functions. Front signaling by means of 8 red LEDs and 16 white LEDs with 39 hours and 12 hours of operating time respectively.

Technical characteristics

Color temperature	White 5,000 K
Usage temperature	From -20°C to 50°C
Electrical insulation	Class III
Weight	592 g
Protection rating	IP68 – IK08
Battery	Li-Ion 7.2 V – 2.6 Ah Chargers C-73 Series
Without signaling	N/A
With signaling	2 push buttons
Housing material	Black technical polymers
Immersion depth	20 m
Light beam	50% at ±2.5° 10% at ±5.5°
Charging status control	Red 0% – 20% Amber 20% – 60% Green 60% – 100% Green flash >100%
Applicable legislation	CE marking (93/68/CEE): 2014/35/EU 2014/30/EU 2011/65/EU


Lighting characteristics

Power	Nominal	High
Luminous flux	100 lm	256 lm
Autonomy	12 h	4 h
Range	105.6 m	240.9
Intensity	5,668 cd	14,510 cd

Functions

Standard programming includes 2 power modes and 2 flashing modes. Automatic shut-off when the handlamp is placed on the charger. Automatic switch-on for 3 minutes in case of mains power failure to the charger.

Dimensions



DATA SHEET. Model: QS-R2B _ Rev. 01 (July 2024)



LUZNOR Desarrollos Electrónicos, S.L.
Paduleta, 47 · 01015 · Vitoria-Gasteiz · 945 200 961
NIF: B01266451 · luznor@luznor.com · www.luznor.com

